


7515 Kraftform Safe-Torque Speed Torque screwdriver, 2-6 Nm, 1/4" x 2.0 Nm x
3.0 Nm x 4.0 Nm x 5.0 Nm x 6.0 Nm x 147.5 mm
Series 7500 Kraftform Safe-Torque Speed Torque Screwdrivers -



| | | | |
|------------------------|---------------|-------------------------------|--------------|
| EAN: | 4013288228314 | Size: | 150x60x35 mm |
| Part number: | 05075815001 | Weight: | 227 g |
| Article number: | 7515 | Country of origin: | CZ |
| | | Customs tariff number: | 82041200 |

- Torque screwdriver with quick torque adjustment
- Easy and quick torque setting
- Fixed position (Torque Lock) for unlimited tightening and loosening moments
- Secure slip-over torque function for clockwise/anti-clockwise torque-control
- Quick and easy setting of the selectable tightening torques (2.0; 3.0; 4.0; 5.0; 6.0 Nm)
- For bits with 1/4" external hexagon drive, also suitable for socket wrench inserts via adapter

For professional screwdriving/fine adjustment AND for torque-controlled screwdriving. Secure slip-over torque mechanism with quick setting for five selectable clockwise/counterclockwise tightening torques (2.0; 3.0; 4.0; 5.0; 6.0 Nm) and one fixed position (Torque Lock) for unlimited loosening and tightening moments. Quick-release holder for high robustness. Suitable for bits with 1/4" external hexagon drive.

Web link

https://products.wera.de/en/torque_tools_series_7500_kraftform_safe-torque_speed_torque_screwdrivers_null_7515.html

Wera - 7515
05075815001 - 4013288228314

Wera Werkzeuge GmbH
Korzeter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

7515 Kraffform Safe-Torque Speed Torque screwdriver, 2-6 Nm, 1/4" x 2.0 Nm x
 3.0 Nm x 4.0 Nm x 5.0 Nm x 6.0 Nm x 147.5 mm
 Series 7500 Kraffform Safe-Torque Speed Torque Screwdrivers -



Five selectable tightening
torques

Simple setting

Excess-load signal



Torque screwdriver with quick
torque adjustment

Five selectable tightening torques
(2.0; 3.0; 4.0; 5.0; 6.0 Nm) and
one fixed position (Torque Lock) for
unlimited tightening and loosening
moments.

Easy setting of the selectable
tightening torques.

Distinctly audible and noticeable
excess-load signal when the pre-
set torque is reached.

Further versions in this product family:



inch



Nm



Nm



Nm



Nm



Nm



mm

| | | | | | | | |
|-------------|------|-----|-----|-----|-----|-----|-------|
| 05075815001 | 1/4" | 2.0 | 3.0 | 4.0 | 5.0 | 6.0 | 147.5 |
|-------------|------|-----|-----|-----|-----|-----|-------|

Web link

https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7515.html

Wera - 7515

05075815001 - 4013288228314

Wera Werkzeuge GmbH

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de