

7510/14 Safe-Torque Speed Tool set for carbide inserts, 14 pieces

Series 7500 Krafftform Safe-Torque Speed Torque Screwdrivers -



EAN: 4013288230683
Part number: 05075840001
Article number: 7510/14

Size: 175x125x61 mm
Weight: 436 g
Country of origin: CZ
Customs tariff number: 82079030


- Particularly suitable for bolting carbide inserts
- Torque screwdriver with quick torque adjustment
- Easy and quick torque setting
- Fixed position (Torque Lock) for unlimited tightening and loosening moments
- Secure slip-over torque function for clockwise/anti-clockwise torque-control
- Quick and easy setting of the selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm)
- For bits with 1/4" external hexagon drive, also suitable for socket wrench inserts via adapter
- Tools with Hex-Plus profile prevent premature rounding of hexagonal socket screws

14-piece tool set. For professional screwdriving/professional fine adjustment AND for torque-controlled screwdriving. Secure slip-over torque mechanism with quick clockwise/counterclockwise setting and five selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm) and one fixed position (Torque Lock) for unlimited loosening and tightening moments. Quick-release holder for high robustness; suitable for bits with 1/4" external hexagon drive. 14 tough bits (25 mm length) for TORX PLUS®, TORX® and hexagonal socket screws. The tool set is particularly suitable for bolting carbide inserts. The Safe-Torque Speed 7510 torque wrench with its five selectable torque values recommended by leading carbide tool manufacturers ensures a reliable torque-controlled screw connection of replaceable carbide inserts.

Web link

https://products.wera.de/en/torque_tools_series_7500_krafftform_safe-torque_speed_torque_screwdrivers_null_7510_14.html

Wera - 7510/14
05075840001 - 4013288230683



For bolting carbide inserts

Five selectable tightening torques

Simple setting



Torque screwdriver with quick torque adjustment

The tool set is particularly suitable for bolting carbide inserts. The Safe-Torque Speed 7510 torque wrench with its five selectable torque values recommended by leading carbide tool manufacturers ensures a reliable torque-controlled screw connection of replaceable carbide inserts.


Five selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm) and one fixed position (Torque Lock) for unlimited tightening and loosening moments.

Easy setting of the selectable tightening torques.

Excess-load signal

Storage and transport

Flexible thanks to hook and loop fastener strips



Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Storage and transport in a robust and compact textile roll bag, so the tool is always close at hand.

The textile box features a fleece zone at the back. Using the provided self-adhesive hook and loop fastener strips, the textile box can be attached to the Wera 2go components. Or to the wall, shelf or workshop trolley.

Web link

https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7510_14.html

Wera - 7510/14
05075840001 - 4013288230683

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

7510/14 Safe-Torque Speed Tool set for carbide inserts, 14 pieces

Series 7500 Kraffform Safe-Torque Speed Torque Screwdrivers -



Set contents:

7510 Kraffform Safe-Torque Speed Torque screwdriver, 1-3 Nm, 1/4" x 1.0 Nm x 1.5 Nm x 2.0 Nm x 2.5 Nm x 3.0 Nm x 147.5 mm

05075810001 1x 1/4" x 1.0 Nm x 1.5 Nm x 2.0 Nm x 2.5 Nm x 3.0 Nm x 147.5 mm



867/1 IP TORX PLUS® bits, 7 IP x 25 mm



05066276001	1x	7 IP x 25 mm
05066278001	1x	8 IP x 25 mm
05066279001	1x	9 IP x 25 mm
05066280001	1x	10 IP x 25 mm
05066282001	1x	15 IP x 25 mm

867/1 TORX® bits, TX 7 x 25 mm



05066494001	1x	TX 7 x 25 mm
05066495001	1x	TX 8 x 25 mm
05066496001	1x	TX 9 x 25 mm
05066485001	1x	TX 10 x 25 mm
05066486001	1x	TX 15 x 25 mm

840/1 Z bits, 2 x 25 mm



05056305001	1x	2 x 25 mm
05056310001	1x	2.5 x 25 mm
05056315001	1x	3 x 25 mm

Web link

https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7510_14.html

Wera - 7510/14
05075840001 - 4013288230683

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de